

Glossary and Sources

Abbreviations

1D	one-dimensional
2D	two-dimensional
AASHTO	American Association of State Highway and Transportation Officials
ADA	Americans with Disabilities Act
AEP	annual exceedance probability
AMC	antecedent moisture condition
ASTM	American Society for Testing and Materials
AWWA	American Water Works Association
BFW	bankfull width
BMP	best management practice
BSTEM	Bank Stability and Toe Erosion Model
Caltrans	California Transportation Department
CCTV	closed-circuit television
CDF	controlled-density fill
CEM	Channel Evolution Model
CFR	Code of Federal Regulations
cfs	cubic foot/feet per second
CIPP	cured-in-place pipe
CLOMR	Conditional Letter of Map Revision
CMP	corrugated metal pipe
CMZ	channel migration zone
CN	curve number
D	diameter
DBH	diameter at breast height
DDP	Design Decision Package
DI	ductile iron (<i>pipe</i>)
DNR	(Washington State) Department of Natural Resources
ECM	Enterprise Content Management

Ecology	Washington State Department of Ecology
EGL	energy grade line
ELJ	engineered log jam
EOE	Office of Equal Opportunity
ERDC	(U.S. Army) Engineer Research and Development Center
FEMA	Federal Emergency Management Agency
FHD	final hydraulic design
FHWA	Federal Highway Administration
FOS	factor of safety
FPSRD	<i>Fish Passage and Stream Restoration Design</i>
FPW	flood-prone width
FRA	Flood Risk Assessment
ft	foot/feet
ft ²	square foot/feet
ft/ft	foot/feet vertical per 1 foot horizontal
ft/s	foot/feet per second
FUR	floodplain utilization ratio
ga	gage
GIS	geographic information system
GPS	Global Positioning System
HATS	Highway Activities Tracking System
HDD	horizontal directional drilling
HDPE	high-density polyethylene
HDS	Hydraulic Design Series
HEC	Hydraulic Engineering Circular
HEC-RAS	Hydrologic Engineering Center's River Analysis System
HGL	hydraulic grade line
HQ	WSDOT Headquarters
HSPF	Hydrological Simulation Program-Fortran
H:V	horizontal:vertical (<i>slope</i>)
HW	headwater
ID	identifier

IDF	intensity, duration, and frequency
in.	inch(es)
Injunction	2013 Federal Court Injunction for Fish Passage
ISPG	<i>Integrated Streambank Protection Guidelines</i>
LiDAR	light detecting and ranging
LOMR	Letter of Map Revision
LTD	long-term degradation
LW	large wood (also known as LWD or LWM)
LWD	large woody debris (also known as LW or LWM)
LWM	large woody material (also known as LWD or LW)
m	meter(s)
m ²	square meter(s)
MDL	master deliverable list
MHHW	mean higher high water
MHO	minimum hydraulic opening
mph	mile(s) per hour
MRI	mean recurrence interval
MW	mobile wood (<i>also known as MWM</i>)
MWM	mobile woody material (<i>also known as MW</i>)
N	newton(s)
NAIP	National Agriculture Imagery Program
NCHRP	National Cooperative Highway Research Program
NHI	National Highway Institute
NLCD	National Land Cover Database
NOAA	National Oceanic and Atmospheric Administration
NRCS	Natural Resources Conservation Service
OHWL	ordinary high water level
oz	ounce(s)
PDF	Portable Document Format
PE	Professional Engineer
PEO	Project Engineer's Office
PHD	preliminary hydraulic design
PP	polypropylene

ppt	part(s) per thousand
PS&E	plans, specifications, and estimates
psi	pound(s) per square inch
PSLC	Puget Sound LiDAR Consortium
PVC	polyvinyl chloride
RCP	reinforced concrete pipe
RCW	Revised Code of Washington
RESP	rock for erosion and scour protection
RHE	Region Hydraulics Engineer
ROW	right-of-way
RSLR	relative sea level rise
SBUH	Santa Barbara Urban Hydrograph
SCR	<i>Scour Certification Record</i>
SCS	Soil Conservation Service
SFHA	special flood hazard area
SFZ	structure-free zone
SR	State Route
SRH-2D	Sedimentation and River Hydraulics – 2D Model
Standard Specifications	<i>Standard Specifications for Road, Bridge, and Municipal Construction Specifications</i>
SWM	small woody material (<i>also known as slash</i>)
TBD	to be determined
T _c	time of concentration
TCE	temporary construction easement
TDA	threshold discharge area
TESC	temporary erosion and sediment control
TSF	ton(s) per square foot
T _t	travel time
USACE	United States Army Corps of Engineers
USBR	United States Bureau of Reclamation
USDA	United States Department of Agriculture
USFS	United States Forest Service
USGS	United States Geological Survey

UV	ultraviolet
WAC	Washington Administrative Code
WCDG	<i>Water Crossing Design Guidelines</i>
WDFW	Washington Department of Fish and Wildlife
WRIA	Water Resource Inventory Area
WSDOT	Washington State Department of Transportation
WSEL	water surface elevation

Main Glossary of Terms

A

abrasion	Wearing or grinding away of material by water laden with suspended material.
access	A means of entering or leaving a public road, street, or highway with respect to abutting property or another public road, street, or highway.
access point	Any point that allows private or public entrance to or exit from the traveled way of a state highway, including “locked gate” access and maintenance access points.
aggradation	Accumulation of sediment deposited by a river or stream.
approach	An access point, other than a public road/street, that allows access to or from a limited access highway on the state highway system.

B

backfill	The soil material used refill the pipe trench after excavation and placement of pipe.
bankfull width	The bankfull channel is defined as the stage when water just begins to overflow into the active floodplain. In channels where there is no floodplain, it is the width of a stream or river at the dominant channel-forming flow.
benefit/cost analysis	A method of valuing a proposition by first monetizing all current expenditures to execute—cost—as well as the expected yields into the future—benefit, then dividing the total benefit by the total cost, thus providing a ratio. Alternatives may be rendered and compared in this fashion where a higher ratio is preferable, indicating a better return on investment.
bicycle	Any device propelled solely by human power upon which a person or persons may ride, having two tandem wheels, either of which is 16 inches or more in diameter, or three wheels, any one of which is more than 20 inches in diameter.
Biologist	One member of the Stream Team (see “Stream Team” in the Glossary). The Biologist shall meet all outlined requirements and certifications listed in Chapter 1 and Chapter 7 and is responsible for the design components of the stream channel listed in Chapter 7 .
bridge	Any structure that is 20 feet or larger in span measured along the centerline of the roadway.
buckling	Failure by an inelastic change in barrel cross-section shape.
bulging	A condition where the pipe wall swells outward or protrudes from the nominal shape.

buried structures

See definition in [Bridge Design Manual](#), Chapter 8.

C

channel complexity

The variation in physical channel components, which may include planform, longitudinal profile, cross-section, sediment distribution, etc.

channel width For the purposes of [Chapter 7](#), channel width is used to describe bankfull width in a situation where the channel is highly influenced by man or heavily degraded conditions exist (WDFW 2013).

circumferential cracking

A crack that occurs perpendicular to the pipe circumference.

clear zone

The total roadside border area, available for use by errant vehicles, starting at the edge of the traveled way and oriented from the outside or inside shoulder (in median applications) as applicable. This area may consist of a shoulder, a recoverable slope, a nonrecoverable slope, and/or a clear run-out area. The clear zone cannot contain a critical fill slope, fixed objects, or water deeper than 2 feet.

climate change vulnerability

The risk that a transportation facility will be impacted by the effects of climate change.

coating

Any material used to protect the integrity of a structural element from the environment.

collector

A context description of a roadway intended to provide a mix of access and mobility performance. Typically low speed, collecting traffic from local roads and connecting them with destination points or arterials. This term is used in multiple classification systems, but is most commonly associated with the *Functional Classification System*.

collector system Routes that primarily serve the more important intercounty, intracounty, and intraurban travel corridors; collect traffic from the system of local access roads and convey it to the arterial system; and on which, regardless of traffic volume, the predominant travel distances are shorter than on arterial routes ([RCW 47.05.021](#)).

consider

To think carefully about, especially in order to make a decision. The decision to document a consideration is left to the discretion of the engineer.

contraction scour

Contraction scour, in a natural channel or at a bridge crossing, involves the removal of material from the bed and banks across all or most of the channel width. This component of scour results from a contraction of the flow area at the bridge, which causes an increase in velocity and shear stress on the bed at the bridge.

contractor	The individual or legal entity contracting with WSDOT for performance of work.
corrosion	Deterioration or dissolution of a material by chemical or electrochemical reaction with its environment.
countermeasure	An action or approach intended to monitor, prevent, delay, or mitigate the severity of hydraulic and/or erosion problems.
crack	A fissure in finished materials.
crimping	The buckling of the metallic shell of a pipe into many small waves along the perimeter of the pipe wall.
critical fill slope	A slope on which a vehicle is likely to overturn. Slopes steeper than 3H:1V are considered critical fill slopes.
crossroad	The minor roadway at an intersection. At a stop-controlled intersection, the crossroad has the stop.
curb section	A roadway cross section with curb and sidewalk.

D

d_c	Critical depth, ft
deliverable	Any unique and verifiable product, result, or capability to perform a service that must be produced to complete a process, phase, or project.
depth of scour	The vertical distance a streambed is lowered by scour below a reference elevation.
design approval	Documented approval of the design at this early milestone locks in design policy for 3 years. Design approval becomes part of the Design Documentation Package (see Design Manual, Chapter 300).
design-bid-build	The project delivery method where design and construction are sequential steps in the project development process (23 CFR 636.103).
design-build contract	An agreement that provides for design and construction of improvements by a consultant/contractor team. The term encompasses design-build-maintain, design-build-operate, design-build-finance, and other contracts that include services in addition to design and construction. Franchise and concession agreements are included in the term if they provide for the franchisee or concessionaire to develop the project that is the subject of the agreement (23 CFR 636.103).
design-builder	The firm, partnership, joint venture, or organization that contracts with WSDOT to perform the work.
design element	Any component or feature associated with roadway design that

becomes part of the final product. Examples include lane width, shoulder width, alignment, and clear zone (see [Design Manual, Chapter 1105](#)).

designed streambed mix

Sediment size distribution that uses pebble counts from the reference reach for the D50 and D84, and an even, designed distribution of sizes for finer classes (USFS 2008).

designer

This term applies to WSDOT design personnel. Wherever “designer” appears in this manual, design-build personnel shall deem it to mean: Engineer of Record, Design Quality Assurance Manager, local programs project design staff, developer project design staff, design-builder, or any other term used in the design-build contract to indicate design-build personnel responsible for the design elements of a design-build project, depending on the context of information being conveyed.

design flood

The discharge that is selected as the basis for the design or evaluation of a hydraulic structure including a hydraulic design flood, scour design flood, and scour check flood.

design methodology

Design methodology has the meaning used in the Washington Department of Fish and Wildlife [Water Crossing Design Guidelines](#).

design reference reach

A stable segment of stream with consistent geometry and planform, that has the slope desired for the designed project reach.

desirable

Design criteria that are recommended for inclusion in the design.

document (verb)

The act of including a short note to the Design Documentation Package that explains a design decision.

driveway

A vehicular access point that provides access to or from a public roadway.

E

easement

A documented right, as a right-of-way, to use the property of another for designated purposes.

element

An architectural or mechanical component or design feature of a space, site, or public right-of-way.

energy grade line (EGL)

The measure of the friction slope or rate of energy head loss due to friction losses from flows along a channel, typically represented at any given point by the sum of the potential energy (i.e., elevation head including bed elevation and flow depth) and the kinetic energy (i.e., velocity head).

F

facility All or any portion of buildings, structures, improvements, elements, and pedestrian or vehicular routes located in a public right-of-way.

Federal Highway Administration (FHWA)

The division of the U.S. Department of Transportation with jurisdiction over the use of federal transportation funds for state highway and local road and street improvements.

final design Any design activities following preliminary design; expressly includes the preparation of final construction plans and detailed specifications for the performance of construction work ([23 CFR 636.103](#)). Final design is also defined by the fact that it occurs after NEPA/SEPA approval has been obtained.

five-hundred-year flood

The flood due to storm and/or tide having a 0.2 percent chance of being equaled or exceeded in any given year. Commonly denoted as Q500.

floodplain utilization ratio (FUR)

The floodplain utilization ratio is the flood-prone width (FPW) (100-year top width) divided by the bankfull width.

freeboard The vertical distance above the water surface elevation (WSEL) that is allowed for waves, surges, drift, and other contingencies.

G

Geomorphologist

One member of the Stream Team (see “Stream Team” in the Glossary). The Geomorphologist shall meet all outlined requirements and certifications listed in [Chapter 1](#) and [Chapter 7](#) and is responsible for the design components of the stream channel listed in [Chapter 7](#).

geotextiles (nonwoven)

A sheet of continuous or staple fibers entangled randomly into a felt for needle-punched nonwovens and pressed and melted together at the fiber contact points for heat-bonded nonwovens. Nonwoven geotextiles tend to have low to medium strength and stiffness with high elongation at failure and relatively good drainage characteristics. The high elongation characteristic gives them superior ability to deform around stones and sticks.

geotextiles (woven)

Slit polymer tapes, monofilament fibers, fibrillated yarns, or multifilament yarns simply woven into a mat. Woven geotextiles generally have relatively high strength and stiffness and, except for the monofilament wovens, relatively poor drainage characteristics.

H

headwater (HW) Depth from inlet invert to upstream total energy grade line, feet.

highway A general term denoting a street, road, or public way for the purpose of vehicular travel, including the entire area within the right-of-way.

hydraulic design flood

The discharge and associated probability of exceedance that reflects the desired level of service for a roadway/bridge crossing a watercourse and/or floodplain. This flood drives the capacity design (i.e., size and configuration) of the waterway opening. By definition, the approach roadway or bridge shall not be inundated by the water levels produced by this flood.

hydraulic height

The minimum height required for hydraulic-related purposes, including freeboard, scour, bed thickness, and appropriate maintenance clearance. Maintenance clearance shall be included in hydraulic height only if necessary to maintain habitat elements.

hydraulic length

The horizontal length along the stream of all components of a structure within 10 feet of the structure-free zone (SFZ) including bridges, culverts, walls, wing walls, and scour countermeasures.

hydraulic opening

Represents the hydraulic width and height necessary to convey the design flood and stream processes.

hydraulic width

The minimum width perpendicular to the creek that is necessary to convey the design flood and stream processes.

I

Injunction, the

United States of America et al., v. State of Washington et al. Permanent Injunction Regarding Culvert Correction, United States District Court, Western District of Washington at Seattle, No. C70-9213 Subproceeding No. 01-1 (Culverts), ordered March 29, 2013.

intersection

An at-grade access point connecting a state highway with a road or street duly established as a public road or public street by the local governmental entity.

Interstate System

A network of routes designated by the state and the FHWA under terms of the federal-aid acts as being the most important to the development of a national system. The Interstate System is part of the principal arterial system.

J

justify

Preparing a memo to the DDP identifying the reasons for the decision: a comparison of advantages and disadvantages of all options considered. A more rigorous effort than document.

K

key pieces

Logs that are large enough to persist and influence hydraulics and bed

topography in a stream through a wide range of flow conditions. Key pieces are independently stable.

L

lane A strip of roadway used for a single line of vehicles.

lane width The lateral design width for a single lane, striped as shown in the [Standard Plans](#) and [Standard Specifications](#). The width of an existing lane is measured from the edge of traveled way to the center of the lane line or between the centers of adjacent lane lines.

large woody material (LWM)

Trees and tree parts where the trunk is larger than 4 inches in diameter and larger than 6 feet in length.

lateral (storm sewer)

These are the first inlets that contribute flow into a storm sewer system.

level of service (LOS)

LOS is based on peak hour, except where noted. LOS assigns a rank (A–F) to facility sections based on traffic flow concepts like density, delay, and/or corresponding safety performance conditions. (See the *Highway Capacity Manual* and AASHTO's *Geometric Design of Highways and Streets* ["Green Book"] for further details.)

M

managing project delivery

A WSDOT management process for project delivery from team initiation through project closing.

meander belt Measurement of the width of a stream's natural meander and planform variability.

median The portion of a divided highway separating vehicular traffic traveling in opposite directions.

minimum hydraulic opening (MHO)

The minimum structure width required by the specialty report and the total height defined by minimum low chord elevation and total scour elevation.

mobile woody material (MWM)

Large woody material that is designed to move at target design flood events.

N

non-erodible Material that is erosion-resistant and not anticipated to degrade or erode significantly over the design life of the structure. Additional guidance and definitions will be provided in future iterations of this manual.

O

one-hundred-year flood

The flood due to storm and/or tide having a 1 percent chance of being equaled or exceeded in any given year. Commonly denoted as Q100.

over-coarsened channel

A constructed channel with a median particle size that is greater than 20 percent larger than the median particle size of the reference reach; is deformable at discharges below the 100-year discharge.

P

Plans, Specifications, and Estimates (PS&E)

The project development activity that follows Project Definition and culminates in the completion of contract-ready documents and the engineer's cost estimate.

project

The Project Management Institute defines a project to be "a temporary endeavor undertaken to create a unique product or service."

project definition(see *Project Summary*)

Project Engineer This term applies to WSDOT personnel. Wherever "Project Engineer" appears in this manual, the design-builder shall deem it to mean "Engineer of Record."

project reach

The segment of stream in which the project is located.

proposal

The combination of projects/actions selected through the study process to meet a specific transportation system need.

purpose

General project goals such as improve safety, enhance mobility, or enhance economic development.

Q

Q

Discharge, cfs.

Q_c

Culvert discharge, cfs.

Q_o

Overtopping discharge over total length of embankment, cfs.

Q_t

Total discharge, cfs.

R

reference reach A stable segment of stream with consistent slope, geometry, planform, and sediment load that represents, to the best available knowledge, the background condition of the project reach (Rosgen 1989).

regrade, channel regrade, natural channel regrade, natural regrade

Each of these terms shall be understood to mean the natural process of a stream to establish an equilibrium slope by means of aggradation or degradation over time. Regrade is expected to effect changes to the stream, its bed and banks, and may include at a minimum, incision, deposition, debris loading, downstream flooding, lateral shifting, and

bank erosion. The regrade process will be set in motion by removal of the existing barrier to fish passage, and is intended to allow the stream to return to its natural channel, by processes that are unencumbered by the design and construction of a new fish-passable stream crossing. Furthermore, the regrade process may extend to areas outside of State right-of-way, although the degree, extent, and timing are unpredictable.

Request for Proposal (RFP)

The document package issued by WSDOT requesting submittal of proposals for the project and providing information relevant to the preparation and submittal of proposals, including the instructions to proposers, contract documents, bidding procedures, and reference documents.

residual pool depth

The difference in depth or bed elevation between a pool and the downstream riffle crest.

right-of-way

A general term denoting land or interest therein, acquired for or designated for transportation purposes. More specifically, lands that have been dedicated for public transportation purposes or land in which WSDOT, a county, or a municipality owns the fee simple title, has an easement devoted to or required for use as a public road/street and appurtenant facilities, or has established ownership by prescriptive right.

road approach

An access point, other than a public road/street, that allows access to or from a limited access highway on the state highway system.

roadway

The portion of a highway, including shoulders.

roughened channel

A constructed channel with streambed material and configuration designed to be non-deformable up to the design discharge.

roundabout

A circular intersection at grade with yield control of all entering traffic, channelized approaches with raised splitter islands, counter-clockwise circulation, and appropriate geometric curvature to force travel speeds on the circulating roadway generally to less than 25 mph.

S

scour

Erosion of streambed or bank material due to flowing water; can be localized around bridge piers and abutments (see long-term degradation as defined in [HEC-18](#), local scour, contraction scour, and total scour).

scour check flood

The discharge associated with the 0.2 percent annual exceedance probability (e.g., 500-year) flood or the 2080 100-year projected flood (whichever is greater).

scour design flood

The discharge associated with the 1 percent annual exceedance probability (e.g., 100-year) flood or the 2080 100-year projected flood (whichever is greater).

shoulder

The portion of the roadway contiguous with the traveled way, primarily for accommodation of stopped vehicles, emergency use, lateral support of the traveled way, and, where allowed, use by pedestrians and bicycles.

site

Parcel(s) of land bounded by a property line or a designated portion of a public right-of-way.

slash

Small trees and parts of trees where the trunk is less than 2 inches in diameter.

small woody material (SWM)

Small trees and parts of trees where the trunk is 4 inches in diameter or smaller.

speed

The operations or target or posted speed of a roadway. There are three classifications of speed established:

- **Low speed** is considered 35 mph and below.
- **Intermediate speed** is considered 40–45 mph.
- **High speed** is considered 50 mph and above.

stable stream

A stream, over time (in the present climate), that transports the flows and sediment produced by its watershed in such a manner that the dimension, pattern, and profile are maintained without either aggrading or degrading (Rosgen 1996).

state highway system

All roads, streets, and highways designated as state routes in compliance with [RCW 47.17](#).

Stream Design Engineer

One member of the Stream Team (see “Stream Team” in the Glossary). The Stream Design Engineer shall meet all outlined requirements and certifications listed in [Chapter 1](#) and [Chapter 7](#) and is responsible for the design components of the stream channel listed in [Chapter 7](#).

stream simulation

The design methodology outlined in the 2013 [Water Crossing Design Guidelines](#) defined as Stream Simulation.

Stream Team

This team is composed of a Stream Design Engineer, a Geomorphologist, and a Biologist that shall lead the day to day effort for designing the stream and its habitat in fish-passable water crossing projects. See definitions for “Stream Design Engineer”, “Biologist”, and “Geomorphologist” for more information. This term applies to

hydraulic design personnel and is used to distinguish the work that is performed using [Chapter 7](#) and [Chapter 10](#) from the rest of the *Hydraulics Manual*. Wherever “Stream Team” appears in this manual, design-build personnel shall deem it to mean: Water Resources Engineer of Record, Design Quality Assurance Manager, design-builder, or any other term used in the design-build contract to indicate design-build personnel responsible for the design elements of a design-build project, depending on the context of information being conveyed.

streambed mix Sediment size distribution that uses pebble counts from the reference reach for the D_{50} and D_{84} and an even, designed distribution of sizes for finer classes (USFS 2008).

structure-free zone (SFZ)

The minimum boundary within which no part of the fish passage structure, including footings, shall be allowed. SFZ incorporates additional width and height beyond the minimum hydraulic opening, not hydraulic related, such as constructability, maintenance access, wildlife connectivity, or other project-specific needs.

superelevation The rotation of the roadway cross section in such a manner as to overcome part of the centrifugal force that acts on a vehicle traversing a curve.

superelevation transition length

The length of highway needed to change the cross slope from normal crown or normal pavement slope to full superelevation.

T

tailwater (TW) Tailwater depth measured from culvert outlet invert, feet.

thalweg Relates to the geometrics of natural or artificial water conveyance channels. More specifically, a thalweg delineates the line connecting the deepest points throughout any given point in a channel.

total scour The sum of long-term degradation, contraction scour, and local scour. Total scour shall be evaluated for all scenarios and flows up to and including the scour design flood and scour check flood that create worst-case total scour.

traveling public Motorists, motorcyclists, bicyclists, pedestrians, and pedestrians with disabilities.

trunk (storm sewer)

The pipes that make up the storm sewer system that are not laterals.

U

urban area An area designated by the Washington State Department of Transportation (WSDOT) in cooperation with the Transportation Improvement Board and Regional Transportation Planning

Organizations, subject to the approval of the FHWA.

urbanized area An urban area with a population of 50,000 or more.

W

Water Crossing Design Guidelines (2013 WCDG)

The 2013 *Water Crossing Design Guidelines*, as published by the Washington Department of Fish and Wildlife at <https://wdfw.wa.gov/publications/01501>. This version of the document has been approved for use on WSDOT projects with exceptions as noted in [Chapter 7](#) and [Chapter 10](#). If a newer version of the document is published, the Hydraulics Section must approve of it prior to use.

Z

- Zone A** FEMA Zone designation. Areas with a 1 percent annual chance of flooding and a 26 percent chance of flooding over the life of a 30-year mortgage. Because detailed analyses are not performed for such areas, no depths or flood elevations are shown within these zones.
- Zone AE** FEMA Zone designation. The base floodplain where base flood elevations are provided. AE Zones are on new format FIRMs instead of A1–A30 Zones.
- Zone A1-30** FEMA Zone designation. These are known as numbered A Zones (e.g., A7 or A14). This is the base floodplain where the FIRM shows a BFE (old format).

Sources

- AASHTO (American Association of State Highway and Transportation Officials). 2017. Standard Specification for Precast Reinforced Concrete Box Sections for Culverts, Storm Drains, and Sewers, January.
- Abbe, T., B. Belby, and F.D. Shields. 2016. Geomorphology and hydrology considerations. Chapter 4 in Bureau of Reclamation and U.S. Army Engineer Research and Development Center. National Large Wood Manual: Assessment, Planning, Design, and Maintenance of Large Wood in Fluvial Ecosystems: Restoring Process, Function, and Structure. 628 p. + Appendix. <http://www.usbr.gov/pn/> and <http://naturaldes.com/resources/>
- Abbe, T., M. Ericsson and L. Embertson. 2015. Channel incision and floodplain abandonment due to historic wood removal in Washington State, USA. International Conference on Wood in World Rivers Conference. University of Padova, Padova, Italy.
- Abbe, T. B., and A. P. Brooks. 2011. "Geomorphic, Engineering, and Ecological Considerations when Using Wood in River Restoration." 419–451 in A. Simon, S. J. Bennett, and J. M. Castro (eds.), *Stream Restoration in Dynamic Fluvial Systems: Scientific Approaches, Analyses, and Tools*. Geophysical Monograph Series 194. Washington, D.C.: American Geophysical Union.
- Abbe, T.B., S. Dickerson-Lange, S., M. Kane, M., P. Cruickshank, P., M. Kaputa, M., and J. Soden, J. 2019. Can wood placement in degraded channel networks result in large-scale water retention? Proceedings of SEDHYD 2019: Conferences on Sedimentation and Hydrologic Modeling, 24-28 June 2019 in Reno, Nevada, USA. Volume 1, pp.408–427.
- Abbe, T. B., and D. R. Montgomery. 1996. "Large Woody Debris Jams, Channel Hydraulics and Habitat Formation in Large Rivers." [https://doi.org/10.1002/\(SICI\)1099-1646\(199603\)12:2<3%3C201::AID-RRR390%3E3.0.CO;2-A](https://doi.org/10.1002/(SICI)1099-1646(199603)12:2<3%3C201::AID-RRR390%3E3.0.CO;2-A)
- Aberle, J. and G. Smart. 2003. The influence of roughness structure on flow resistance on steep slopes. *Journal of hydraulic research* 41(3), 259–269.
- American Whitewater. 2019. www.americanwhitewater.org.
- Anderson, Paul S., Susan Meyer, Dr. Patricia Olson, Erik Stockdale. 2016. Determining the Ordinary High Water Mark for Shoreline Management Act Compliance in Washington State. Washington State Department of Ecology, Olympia, Washington.
- Annandale, G. W. 2006. "Review of scour technology."
- ASTM (American Society for Testing and Materials). 2016. C1433-16b, Standard Specification for Precast Reinforced Concrete Monolithic Box Sections for

- Culverts, Storm Drains, and Sewers, ASTM International, West Conshohocken, Pennsylvania. www.astm.org.
- Baird, D. C., L. Fotherby, C. C. Klumpp, and S. M. Sculock. 2015. *Bank Stabilization Design Guidelines*. U.S. Department of the Interior, Bureau of Reclamation, Technical Service Center, Denver, Colorado.
- Barnes, H. H. 1967. *Roughness characteristics of natural channels*. US Geological Survey Water-Supply Paper 1849. U.S. Government Printing Office.
- Bartels, R., J. D. Dell, R. L. Knight, G. Schaefer. 1985. "Dead and Down Woody Material." *Management of Wildlife and Fish Habitats in Forests of Western Oregon and Washington*. USDA Forest Service. Portland, Oregon.
- Chow, V. T. 1959. Open-channel hydraulics. McGraw-Hill civil engineering series.
- Bathurst, J. C. 1985. Flow resistance estimation in mountain rivers. *Journal of Hydraulic Engineering* 111(4), 625–643.
- Bathurst, J. C. 1987. "Critical conditions for bed material movement in steep, boulder-bed streams." International Association of Hydrological Sciences Publication 165: 309–318.
- Bilby, Robert E., and Gene E. Likens. "Importance of organic debris dams in the structure and function of stream ecosystems." *Ecology* 61, no. 5 (1980): 1107-1113.
- Booth, D. 1990. Stream-Channel Incision Following Drainage-Basin Urbanization. *Water Resources Research*. American Water Resources Association. 26(3) 407–417.
- Borah D. K. 1989. Scour-depth prediction under armoring conditions. *Journal of Hydraulic Engineering*, ASCE Vol. 115, No. 10.
- Braudrick, C. A., and G. E. Grant. 2000. "Why Do Logs Move In Rivers?" *Water Resources Research* 36-2, John Wiley & Sons, LTD.
- Braudrick, C. A., G. E. Grant, Y. Ishiharu, and H. Ikeda. 1997. "Dynamics of Wood Transport in Streams: A Flume Experiment." *Earth Surface Processes and Landforms*. 22: 669–683.
- Bretschko, Gernot. "The dynamic aspect of coarse particulate organic matter (CPOM) on the sediment surface of a second order stream free of debris dams (RITRODAT-LUNZ study area)." *Hydrobiologia* 203, no. 1-2 (1990): 15-28.
- Brooks, A.P., Brierley, G.J. and Millar, R.G. 2003. The long-term control of vegetation and woody debris on channel and floodplain evolution: insights from a paired catchment study between a pristine and disturbed lowland alluvial river in southeastern Australia. *Geomorphology* 51, 7–29.

- Brooks, A.P., T. Abbe, T. Cohen, N. Marsh, S. Mika, A. Boulton, T. Broderick, D. Borg, and I. Rutherford. 2006. Design guideline for the reintroduction of wood into Australian streams. Land & Water, Australia, Canberra.
- Brummer, C.J., Abbe, T.B., Sampson, J.R. and Montgomery, D.R. 2006. Influence of vertical channel change associated with wood accumulations on delineating channel migration zones, Washington, USA. *Geomorphology* 80, 295–309.
- Bunte, Kristin; Abt, Steven R. 2001. Sampling surface and subsurface particle-size distributions in wadable gravel- and cobble-bed streams for analyses in sediment transport, hydraulics, and streambed monitoring. Gen. Tech. Rep. RMRS-GTR-74. Fort Collins, Colorado: U.S. Department of Agriculture, Forest Service, Rocky Mountain Research Station. 428 p.
- Castro, J. 2003. Geomorphologic Impacts of Culvert Replacement and Removal: Avoiding Channel Incision; Unpublished Report. U.S. Fish and Wildlife Service: Portland, Oregon.
- Castro, J.M. and A. Beavers. 2016. Providing Aquatic Organism Passage in Vertically Unstable Streams. *Water* 8(133), doi:10.3390/w8040133.
- Castro, Janine M., and Colin R. Thorne. 2019. "The stream evolution triangle: Integrating geology, hydrology, and biology." *River Research and Applications* 35, No. 4: 315–326.
- Cluer, Brian, and Colin Thorne. 2013. "A stream evolution model integrating habitat and ecosystem benefits." *River Research and Applications* 30, No. 2: 135–154.
- Collins, B.D., D.R. Montgomery, and A.D. Haas, 2002. Historical Changes in the Distribution and Functions of Large Wood in Puget Lowland Rivers. *Canadian Journal of Fisheries and Aquatic Sciences* 59:66–76.
- Cramer, M.L. (managing editor). 2012. *Stream Habitat Restoration Guidelines*. Co-published by the Washington Departments of Fish and Wildlife, Natural Resources, Transportation and Ecology, Washington State Recreation and Conservation Office, Puget Sound Partnership, and the U.S. Fish and Wildlife Service. Olympia, Washington.
- D'Aoust, S. G. 1991. "Large Woody Debris Fish Habitat Structure Performance and Ballasting Requirements." Master of Applied Science Thesis, University of Ottawa. Revised 1999.
- D'Aoust, S. G., and R. G. Millar. 2000. "Stability of Ballasted Woody Debris Habitat Structures." *Journal of Hydraulic Engineering*. November.
www.wsdot.wa.gov/publications/manuals/fulltext/M23-03/M23-03.05Revision.pdf.
- Dey, Subhasish. 2014. *Fluvial Hydrodynamics: Hydrodynamic and Sediment Transport Phenomena*. Fluvial Processes: Meandering and Braiding.

- Diehl, T. H., and B. A. Bryan. 1993. Supply of Large Woody Debris in a Stream Channel. *Hydraulic Engineering*, 1055.
- Dolloff, C. Andrew, and Jackson R. Webster. "Particulate organic contributions from forests and streams: debris isn't so bad." In: Verry, Elon S.; Hornbeck, James W.; Dolloff, C. Andrew, eds. *Riparian management in forests of the continental Eastern United States*. Boca Raton, FL: Lewis Publishers, CRC Press LLC: 125-138. (2000).
- Downs, P.W. and Piégay, H. 2019. Invited review: Catchment-scale cumulative impact of human activities on river channels in the late Anthropocene: implications, limitations, prospect. *Geomorphology*. 338, 88–104.
- Ecology (Washington State Department of Ecology). 2003. A Framework for Delineating Channel Migration Zones. Ecology Publication 03-06-027 (Final Draft). November. <https://apps.ecology.wa.gov/publications/documents/0306027.pdf>
- . 2014. Channel Migration Toolbox: ArcGIS® Tools for Measuring Stream Channel Migration. Publication 14-06-032. October. <https://apps.ecology.wa.gov/publications/documents/1406032.pdf>
- . 2015. Screening Tools for Identifying Migrating Stream Channels in Western Washington: Geospatial Data Layers and Visual Assessments. Publication 15-06-003. February. <https://apps.ecology.wa.gov/publications/documents/1506003.pdf>
- . 2019. *Stormwater Management Manual for Western Washington*. Publication 19-10-021. <https://apps.ecology.wa.gov/publications/SummaryPages/1910021.html>.
- FHWA (Federal Highway Administration). 2005. "Debris Control Structures; Evaluation and Countermeasures, Third Edition." *Hydraulic Engineering Circular No. 9*, Publication FHWA- IF-04-016. U.S. Department of Transportation, Washington, D.C.
- . 2006. "Hydraulic Design of Energy Dissipators for Culverts and Channels, Third Edition." *Hydraulic Engineering Circular No. 14*, Publication FHWA-NHI-06-086. U.S. Department of Transportation, Washington, D.C.
- . 2009. "Bridge Scour and Stream Instability Countermeasures: Experience, Selection, and Design Guidance, Third Edition." *Hydraulic Engineering Circular No. 23*, Publication FHWA-NHI-09-111. U.S. Department of Transportation, Washington, D.C.
- . 2009. "Urban Drainage Manual, Third Edition." *Hydraulic Engineering Circular No. 22*, Publication FHWA-NHI-10-009. U.S. Department of Transportation, Washington, D.C.

- . 2010. “Culvert Design for Aquatic Organism Passage” *Hydraulic Engineering Circular No. 26*, Publication FHWA-HIF-11-008. U.S. Department of Transportation, Washington, D.C.
- . 2012. “Design of Roadside Channels with Flexible Linings, Third Edition.” *Hydraulic Engineering Circular No. 15*, Publication FHWA-HIF-12-004. U.S. Department of Transportation, Washington, D.C.
- . 2012. “Evaluating Scour at Bridges, Fifth Edition.” *Hydraulic Engineering Circular No. 18*, Publication FHWA-HIF-12-003. U.S. Department of Transportation, Washington, D.C.
- . 2012. “Stream Stability at Highway Structures, Fourth Edition.” *Hydraulic Engineering Circular No. 20*, Publication FHWA-HIF-12-004. U.S. Department of Transportation, Washington, D.C.
- . 2016. “Highways in the River Environment: Floodplains, Extreme Events, Risk, and Resilience.” *Hydraulic Engineering Circular No. 17*, Publication FHWA-HIF-16-018. U.S. Department of Transportation, Washington, D.C.
- . 2019. *Two-Dimensional Hydraulic Modeling for Highways in the River Environment*. Publication FHWA-HIF-19-061. October.
<https://www.fhwa.dot.gov/engineering/hydraulics/pubs/hif19061.pdf>.
- . 2020. “Highways in the Coastal Environment: Third Edition.” *Hydraulic Engineering Circular No. 25*, Publication FHWA-HIF-19-059. U.S. Department of Transportation, Washington, D.C.
- . 2020. *FHWA Tech Brief “Hydraulic Considerations for Shallow Abutment Foundations.”* Office of Bridges & Structures. Publication FHWA-HIF- 19-007. December 15 (originally published December 21, 2018).
<https://www.fhwa.dot.gov/engineering/hydraulics/pubs/hif19007.pdf>.
- . 2021. *FHWA Tech Brief “Pier Scour Estimation for Tsunami at Bridges.”* Office of Bridges & Structures. Publication FHWA-HRT-21-073. August.
<https://www.fhwa.dot.gov/publications/research/infrastructure/structures/bridge/21073.pdf>.
- . 2023a. *FHWA Tech Brief “Hydraulic Considerations for Abutments on Deep Foundations and Bridge Embankment Protection.”* Office of Bridges & Structures. Publication FHWA-HIF-23-048. September.
<https://www.fhwa.dot.gov/engineering/hydraulics/pubs/hif23048.pdf>.
- . 2023b. *Highways in the River Environment: Roads, Rivers, and Floodplains, Second Edition*. Publication FHWA-HIF-23-004. Hydraulic Engineering Circular No. 16. January.

https://www.fhwa.dot.gov/engineering/hydraulics/library_arc.cfm?pub_number=2&id=185.

Flanagan, S. A. 2003. "How Culverts Fail."

———. 2005. "Woody Debris Transport at Road-Stream Crossings." *Stream Notes*. USDA, Forest Service. Stream Systems Technology Center - Rocky Mountain Research Station. Fort Collins, Colorado.

https://www.fs.usda.gov/biology/nsaec/assets/sn_10_05.pdf October.

Fouty, Tyler. "Flume-Based Design Recommendations for Deformable Grade Control in Stream Simulation Culverts." Microsoft Teams Presentation, March 10, 2023.

Fox, M. J. 2003. *Spatial Organization, Position, and Source Characteristics of Large Woody Debris in Natural Systems*. Doctoral dissertation, University of Washington, Seattle, WA. Copyright 2003 by ProQuest Information and Learning Company, Ann Arbor, Michigan, UMI No. 3102652.

Fox, M., and S. Bolton. 2007. A regional and geomorphic reference for quantities and volumes of instream wood in unmanaged forested basins of Washington State. *North American Journal of Fisheries Management* 27:342–359.

Furniss, M. J., T. S. Ledwith, M. A. Love, B. C. McFadin, and S. A. Flanagan. 1998. *Response of Road-Stream Crossings to Large Flood Events in Washington, Oregon, and Northern California*. USDA, Forest Service. San Dimas Technology and Development Center. San Dimas, California. https://www.fs.usda.gov/t-d/pubs/html/wr_p/98771807/98771807.htm

Gardner, James W. 1983. *Experimental study of knickpoint and longitudinal profile evolution in cohesive, homogeneous material*. Department of GeoSciences, The Pennsylvania State University.

Griffiths, G. A. 1981. Flow resistance in coarse gravel bed rivers. *Journal of the Hydraulics Division* 107(7), 899–918.

Hanson, Heather. 2022. *Culvert Design Guidelines for Ecological Function*. U.S. Fish and Wildlife Service. Updated March 14, 2022. <https://www.fws.gov/alaska-culvert-design-guidelines>

Hey, R. D. 1979. Flow resistance in gravel-bed rivers. *Journal of the Hydraulics Division* 105(4), 365–379.

Hutchinson, I. 1988. *Salinity tolerance of plants of estuarine wetlands and associated uplands*. Report to the Washington State Shorelands and Coastal Zone Management Program. Contract C0088137. Simon Fraser University, Burnaby, British Columbia.

- Jarrett, R. D. 1984. Hydraulics of high-gradient streams. *Journal of Hydraulic Engineering* 110(11), 1519–1539.
- Johnson, A. W., and J. M. Stypula (eds.). 1993. *Guidelines for Bank Stabilization Projects in the Riverine Environments of King County*. King County Department of Public Works, Surface Water Management Division. Seattle, Washington.
- Johnson, P.A. 2006. Assessing Stream Channel Stability at Bridges in Physiographic Regions. Federal Highway Administration Office of Infrastructure Research and Development. Publication FHWA-HRT-05-072.
- Kondolf, M. G, and T. E. Lisle. 2016. “Measuring bed sediment,” chap. 13 in *Tools in Fluvial Geomorphology*. M. G. Kondolf and M. H. Piégay, eds., 278–305. John Wiley & Sons, Ltd.
- Kramer, Natalie, and Ellen Wohl. 2016. “Rules of the Road: A Qualitative and Quantitative Synthesis of Large Wood Transport Through Drainage Networks.” *Geomorphology*, 279. 10.1016/j.geomorph.2016.08.026.
- Kuichling, E. 1889. “The Relation Between the Rainfall and the Discharge of Sewers in Populous Districts.” *Transactions, American Society of Civil Engineers* 20, 1–56.
- Lagasse, P.F., P. E. Clopper, L. W. Zevenbergen, and J. F. Ruff. 2006. *Riprap Design Criteria, Recommended Specifications, and Quality Control*. NCHRP Report 568, Transportation Research Board, Washington, D.C.
http://onlinepubs.trb.org/onlinepubs/nchrp/nchrp_rpt_568.pdf.
- Lagasse, P.F., P. E. Clopper, L. W. Zevenbergen, W. J. Spitz, and L. G. Girard. 2010. “Effects of Debris on Bridge Pier Scour.” *NCHRP Report 653*, Transportation Research Board, Washington, D.C. doi: 10.17226/22955.
- Lane, E.W. Design of stable alluvial channels. *Trans. Am. Soc. Civ. Eng.* 1955. 120, 1234–1260.
- Lee, A. J. and R. I. Ferguson. 2002. Velocity and flow resistance in step-pool streams. *Geomorphology* 46(1-2), 59–71.
- Limerinos, J. T. 1970. Determination of the manning coefficient from measured bed roughness in natural channels. *Geologic Survey Water-Supply Paper 1898-B*. U.S. Government Printing Office.
- Liu, X., Mahdavi, A., Zevenbergen, L. and Kramer, C. 2024. *Selection and Application of Mannings’s Roughness Values in Two-Dimensional Hydraulic Models*. NCHRP Report 1077, Transportation Research Board, Washington, D.C.
<https://www.trb.org/Publications/Blurbs/183186.aspx>
- Mackin, J.H., 1948. Concept of a graded river. *Geological Society of America Bulletin* 59, 463–511.

- Marden, M., Arnold, G., Gomez, B. and Rowan, D. 2005. Pre- and post-reforestation gully development in the Mangatu Forest, East Coast, North Island, New Zealand. *River Research and Applications* 21, 757–771.
- Mastin, M. C., C. P. Konrad, A. G. Veilleux, and A. E. Tecca. 2016. *Magnitude, Frequency, and Trends of Floods at Gaged and Ungaged Sites in Washington, Based on Data through Water Year 2014* (ver 1.2, November 2017): USGS Scientific Investigations Report 2016–5118, 70 p., <http://dx.doi.org/10.3133/sir20165118>.
- MGS Software. 2018. MGSFlood. <http://www.mgsengr.com/mgsfloodhome.html>.
- Miller, J. F., R. H. Frederick, and R. J. Tracey. 1973. *Precipitation–Frequency Atlas of the Western United States*. National Oceanic and Atmospheric Administration, U.S. Department of Commerce, Washington, D.C.
- Miller, I.M., H. Morgan, G. Mauger, T. Newton, R. Weldon, D. Schmidt, M. Welch, and E. Grossman. 2018. *Projected Sea Level Rise for Washington State – A 2018 Assessment*. A collaboration of Washington Sea Grant, University of Washington Climate Impacts Group, University of Oregon, University of Washington, and U.S. Geological Survey. Prepared for the Washington Coastal Resilience Project. Updated July 2019.
- Montgomery, D. R., and J. M. Buffington. 1993. *Channel Classification, Prediction of Channel Response, and Assessment of Channel Conditions*. Timber, Fish & Wild-Life Publication TFW-SH10-93-002.
- Montgomery, D. R., Buffington, J. M. 1997. Channel-reach morphology in mountain drainage basin. *GSA Bulletin*; May; v. 109; no. 5; p. 596–611.
- Montgomery, D.R. and Abbe, T.B. 2006. Influence of logjam-formed hard points on the formation of valley-bottom landforms in an old-growth forest valley, Queets River, Washington, USA. *Quaternary Research* 65, 147–155.
- Mount, J.F. 1995. *California Rivers and Streams*. University of California Press. Berkeley, California.
- NCHRP (National Cooperative Highway Research Program). 2004. Report 533: Handbook for Predicting Stream Meander Migration. Transportation Board of the National Academies. https://www.trb.org/publications/nchrp/nchrp_rpt_533.pdf
- NRCS (National Resources Conservation Service). 2007. *Stream Restoration Design National Engineering Handbook* 654. U.S. Department of Agriculture, Washington, D.C.
- . 2010. *National Engineering Handbook Part 630 Hydrology*. U.S. Department of Agriculture, Washington, D.C.
- . n.d. NRCS Snow Map, <https://wrcc.dri.edu/summary/climsmwa.html>.

- Phelps, J.D., 2011. The Geomorphic Legacy of Splash Dams in the Southern Oregon Coast Range. University of Oregon.
- Pollock, M.M., Beechie, T.J. and Jordan, C.E. 2007. Geomorphic changes upstream of beaver dams in Bridge Creek, an incised stream channel in the interior Columbia River basin, eastern Oregon. *Earth Surface Processes and Landforms* 32, 1174–1185.
- Pollock, M.M., T.J. Beechie, J.M. Wheaton, C.E. Jordan, N. Bouwes, N. Weber, and C. Volk, 2014. Using Beaver Dams to Restore Incised Stream Ecosystems. *BioScience* 64:279–290.
- Pollock, M.M., J.M. Wheaton, N. Bouwes, C. Volk, N. Weber, and C.E. Jordan, 2012. Working with Beaver to Restore Salmon Habitat in the Bridge Creek Intensively Monitored Watershed Design Rationale and Hypotheses. Seattle, Washington.
- Powers, Paul D., Matt Helstab, and Sue L. Niezgoda. 2019. “A process-based approach to restoring depositional river valleys to Stage 0, an anastomosing channel network.” *River Research and Applications* 35, no. 1: 3–13.
- Prosser, I.P. and Soufi, M. 1998. Controls on gully formation following forest clearing in a humid temperate environment. *Water Resources Research* 34 (12), 3661–3671.
- Rafferty, M. 2016. *Computational Design Tool for Evaluating the Stability of Large Wood Structures*. Technical Note TN-103.2. Fort Collins, Colorado: U.S. Department of Agriculture, Forest Service, National Stream and Aquatic Ecology Center. 27 p.
- Rickenmann, D. and A. Recking. 2011. Evaluation of flow resistance in gravel-bed rivers through a large field data set. *Water Resources Research* 47(7).
- Rosgen, D.H. 1989. The Reference Reach: A Blueprint for Natural Channel Design. *Engineering Approaches to Ecosystem Restoration*: pp. 1009-1016.
- Rosgen, D.L. 1996. *Applied River Morphology*. Wildland Hydrology Books, Pagosa Springs.
- Ruiz-Villanueva, V., H. Piégay, A. M. Gurnell, R. A. Marston, and M. Stoffel. 2016. “Recent Advances Quantifying the Large Wood Dynamics in River Basins: New Methods and Remaining Challenges.” *Reviews of Geophysics*. 54,611–652.
<https://agupubs.onlinelibrary.wiley.com/doi/full/10.1002/2015RG000514>.
- Schanz, A.A, Montgomery, D.R., Collins, B. 2019. Anthropogenic strath terrace formation caused by reduced sediment retention. *PNAS*, 116(18) 8734–8739.
- Schumm, S.A.; Harvey, M.; Watson, C. 1984. *Incised Channels: Morphology, Dynamics, and Control*; Water Resources Publications: Littleton, Colorado.
- Sear, D.A., Millington, C.E., Kitts, D.R. and Jeffries, R. 2010. Logjam controls on channel: floodplain interactions in wooded catchments and their role in the formation of multi-channel patterns. *Geomorphology* 116, 305–319.

- Shahverdian, Scott & Wheaton, Joseph & Bennett, Stephen & Bouwes, Nick & Camp, Reid & Jordan, Chris & Portugal, Elijah & Weber, Nick. (2019). Chapter 4 – Mimicking and Promoting Wood Accumulation and Beaver Dam Activity with Post-Assisted Log Structures and Beaver Dam Analogues. 10.13140/RG.2.2.22526.64324.
- Simon, A.; Rinaldi, M. 2000. Channel instability in the loess area of the Midwestern United States. *J. Am. Water Resour. Assoc.*, 36, 133–150.
- Simon, A.; Rinaldi, M. Disturbance, stream incision, and channel evolution: The roles of excess transport capacity and boundary materials in controlling channel response. *Geomorphology*. 79, 361–383.
- Simon, A., R. Thomas, A. Curini, and N. Bankhead. 2009. “Bank stability and toe erosion model (BSTEM) Static version 5.2.”
- Skidmore, P.B., C.R. Thorne, B.L. Cluer, G.R. Pess, J.M. Castro, T.J. Beechie, and C.C. Shea. 2011. Science base and tools for evaluating stream engineering, management, and restoration proposals. U.S. Dept. Commerce, NOAA Tech. Memo. NMFS-NWFSC-112, 255 p.
- Stock, J.D., Montgomery, D.R., Collins, B.D., Dietrich, W.E. and Sklar, L. 2005. Field measurements of incision rates following bedrock exposure: implications for process controls on the long profiles of valleys cut by rivers and debris flows. *Geological Society of America Bulletin* 117 (11/12), 174–194.
- Stubchaer, J. M. 1975. “The Santa Barbara Urban Hydrograph Method,” in *Proceedings of National Symposium on Urban Hydrology and Sediment Control*. University of Kentucky, Lexington, Kentucky, 131–141.
- USBR (United States Bureau of Reclamation). 2014. *Large Woody Material—Risk-Based Design Guidelines*. Knutson, P.E., and Fealko, P.E., co-authors, USBR Pacific Northwest Region Boise, Idaho. 115 p.
- USBR and ERDC (United States Bureau of Reclamation and U.S. Army Engineer Research and Development Center). 2016. *National Large Wood Manual: Assessment, Planning, Design, and Maintenance of Large Wood in Fluvial Ecosystems: Restoring Process, Function, and Structure*.
https://www.usbr.gov/research/projects/download_product.cfm?id=2219 (click on “River Restoration,” then “Techniques”).
- USDA (United States Department of Agriculture). 2008. *Stream Simulation: An Ecological Approach to Providing Passage for Aquatic Organisms at Road-Stream Crossings*, Appendix E.
- USDOT (United States Department of Transportation). 2008. “Introduction to Highway Hydraulics.” *Hydraulic Design Series 4*, Publication FHWA-NHI-08-090. U.S. Department of Transportation, Washington, D.C.

- . 2012a. “Hydraulic Design of Highway Culverts, Third Edition.” *Hydraulic Design Series* 5, Publication FHWA-HIF-12-026m. U.S. Department of Transportation, Washington, D.C.
- . 2012b. “Hydraulic Design of Safe Bridges.” *Hydraulic Design Series* 7, Publication FHWA-HIF-12-018. U.S. Department of Transportation, Washington, D.C.
- . 2016. HY-8 Culvert Hydraulic Analysis Program software, Version 7.50. U.S. Department of Transportation, Washington, D.C.
www.fhwa.dot.gov/engineering/hydraulics/software/hy8/. Build date July 28.
- USFS (United States Forest Service). 2008. Stream Simulation: An Ecological Approach to Providing Passage for Aquatic Organisms at Road-Stream Crossings, National Technology and Development Program, San Dimas, CA 91773.
- USGS (United States Geological Survey). n.d. PeakFQ website:
<https://water.usgs.gov/software/PeakFQ>.
- . n.d. StreamStats website: <https://streamstats.usgs.gov/ss>.
- . n.d. Surface-Water Data for Washington Website: <https://streamstats.usgs.gov/ss>. Washington Climate Summaries. n.d., Western Regional Climate Center Webpage, <https://wrcc.dri.edu/summary/climsmwa.html>.
- WDFW (Washington Department of Fish and Wildlife). 2002. *Integrated Streambank Protection Guidelines*. Washington State Aquatic Habitat Guidelines Program, Olympia, Washington.
- . 2013. *Water Crossing Design Guidelines*. Olympia, Washington, 300 p.
- . 2016a. *Incorporating Climate Change into the Design of Water Crossing Structures; Final Project Report*. Habitat Program—Science Division, Olympia, Washington, 300 p.
- Whiting, Peter J., and William E. Dietrich. 1993. “Experimental constraints on bar migration through bends: Implications for meander wavelength selection.” *Water Resources Research* 29, no. 4: 1091–1102.
- Wolman, M. G. 1954. “A Method of Sampling Coarse River-Bed Material.” *Transactions—American Geophysical Union*, 35, 951–956.
- WSDOT (Washington State Department of Transportation). 2011. *Climate Impacts Vulnerability Assessment*. November.
- . 2019a. Utilities Manual M 22-87.10. Engineering and Regional Operations, Development Division, Design Office. February 28.
- . 2019b. *Highway Runoff Manual* M 31-16.05. Engineering and Regional Operations, Development Division, Design Office. Supplement May 22.

- . 2019c. *Development Services Manual* M 3007-01, Engineering and Regional Operations, Development Division, Design Office. October 28.
 - . 2020. *Design Manual* M 22-01.19. Engineering and Regional Operations, Development Division, Design Office. September.
 - . 2021a. *Local Agency Guidelines* M 36-63.36. Local Programs, Engineering Services. June 22.
 - . 2021b. *Design-Build Manual* M 3126.02. Construction Division. Design-Build Office. August 9.
 - . 2021c. *Standard Specifications for Road, Bridge, and Municipal Construction* M 41-10. August 22.
 - . 2021d. *Standard Plans* M 21-01. Engineering and Regional Operations, Development Division, Design Office. September 21.
- Yochum, S. E., B. P. Bledsoe, G. C. David, and E. Wohl. 2012. Velocity prediction in high-gradient channels. *Journal of Hydrology* 424, 84–98..